



YANMAR

7177 30th Ave. North, St Petersburg, FL 33710 Phone: 800-545-4574, Georgia 229-347-8394 Fax: 727-381- 3235 www.maspowerproducts.com

PORTABLE

Series

2.7 - 5.5 kW

- ★ Standard with powder coated frame
- ★ Superior durability
- ★ Compression release



MP3700 (standard) shown

MP Diesel Generator

Air Cooled Diesel Generator Specification (EPA Certified)

Generator Spec.			Model	Open Type		
			MP2700	MP3700	MP5500	
Type			Brushless			
Frequency		Hz	60			
Output	AC	Max. kW	2.7	3.7	5.5	
		Rated kW	2.5	3.5	5.0	
Engine Model		Yanmar	L48V	L70V	L100V	
Engine Output		Max Hp	4.7 @ 3600	6.7 @ 3600	10 @ 3600	
Rated Voltage		V	120	120	120/240	
Rated Current		A	20.8	29.2 / 14.6	41.7 / 20.8	
Voltage Control System			Capacitor Regulated			
Rotation Speed		rpm	3600			
Number of Phases			Single Phase			
Number of Poles			2 Pole			
Power Factor			Unity 1.0			
Insulation Class			Class E			
Bearing Type			Ball bearing (seal type)			
Output receptacle	AC	V-A	(2) 120 Duplex	(1) 120 Duplex		
				(1) 120 Twistlock	(1) 240 Twistlock	
Breaker		AC	(1) Breaker	(2) Breakers	(2) Breakers	
Generator Size (LxWxH)		Inches	27x21x24	27x21x24	27x21x24	
Weight		LBS	141	181	243	

Options

- Electric start with key switch
- Low oil Shutdown on electric start models
- 16" Pneumatic wheel kit
- Larger Fuel tank for longer run capacity